

## DMW Syntho SAE 10W-40

Advanced Performance Synthetic Based Engine Oil

### Application:

High quality synthetic based engine oil formulated with hydrocracked components. Recommended for passenger cars and vans equipped with modern diesel, gasoline or LPG engines with catalyts. Suitable for normally aspirated or turbo charged engines.

### Feature and Benefits:

- Good engine protection after cold starting
- Synthetic based year round engine lubricant
- Reduces engine fuel consumption
- High viscosity index providing strong lubricant film at all operating conditions
- Good engine performance under different driving circumstances
- Good protection against rust and corrosion
- Prevents formation of black sludge
- Catalyst friendly lubricant

### Specifications :

ACEA A3;  
ACEA B3;  
API SL/CF;  
MB 229.1;  
VW 505.00;

PROPERTIES	METHOD	UNIT	TYPICAL
Viscosity Grade			SAE 10W-40
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	874
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.5
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	98.4
Viscosity Index	D 2270		152
Borderline Pumping Temperature	D 3829	°C	-30.2
Pour Point	D 97	°C	-30
Flash Point	D93	°C	202

The figures above are not a specification. They are typical figures obtained within production tolerances.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.