

## DMW Evo-Max SAE 5W-30

Fully Synthetic Engine Oil for Diesel and Gasoline Engines with or without Turbo

### Product Description:

DMW Evo-Max SAE 5W-30 is a fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. DMW additive technology reduces carbon or sludge build up even under severe driving conditions.

DMW Evo-Max SAE 5W-30 is manufactured using the highest quality Fully Synthetic base stocks and state of the art DMW additive technology. This ensures a finished product with an unmatched performance level.

Designed for advanced passenger car gasoline and diesel engines, both turbocharged and non-turbo-charged including engines with diesel particle filters (ACEA C3)

### Specifications :

ACEA C3; API SP; BMW LL-04\*; MB 229.51; Porsche C30; VW 504 00/507 00\*

CHARACTERISTIC	METHOD	UNIT	RESULT
Appearance	Visual	-	Bright & Clear
ASTM Colour	ASTM D1500	-	<L3.5
Density @15°C	ASTM D4052	kg/m <sup>3</sup>	0.863
Kinematic Viscosity @40°C	AST D445	cSt	74.6
Kinematic Viscosity @100°C	ASTM D445	cSt	11.9
Viscosity Index	ASTM D2270	-	160
Total Base Number	ASTM D2896	mg KOH/g	8.6
Flash Point (COC)	ASTM D92	°C	269
Pour Point	ASTM D97	°C	-44
CCS Viscosity @ -20 °C	ASTM D5293-14	mPa.s	3950

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.