

DMW Execell-Max SAE 5W-40

Fully Synthetic Racing Engine Oil for All Modern Engines

Product Description:

DMW Execell-Max 5W-40 100% Fully Synthetic formulation against friction, heat and corrosion, keeping engines healthy and efficient. DMW additives reduces carbon and sludge build up even under severe driving conditions.

Excellent range of applications; ranging from K class engines to WTI/ VTEC engines to European Engines. Also appropriate for use in turbo-charged cars giving improved engine quietness and reduced emissions. Sustained horsepower and torque throughout the life of your engine with regular use.

Feature and Benefits:

- DMW additives reduces deposits and sludge build up
- Fully synthetic formula provides outstanding wear protection and superior thermal and oxidation stability for extended oil drain interval according to manufacturer recommendation
- excellent cold start properties for fast engine protection

Specifications :

API SP; ACEA A3/B3/B4; MB 229.5; VW 502 00/ 505 00*; Renault 0700/0710; GM-LL-B-025; BMW LL-01; Porsche A40; PSA B712296

Typical Properties:

SAE Grade: **5W-40**

CHARACTERISTIC	METHOD	UNIT	RESULT
Appearance	Visual	-	Bright & Clear
Color	ASTM D1500	-	2.2
Density @15°C	ASTM D4052	kg/L	0.8560
Kinematic Viscosity @40°C	AST D445	cSt	77.35
Kinematic Viscosity @100°C	ASTM D445	cSt	13.26
Viscosity Index	ASTM D2270	-	175
Flash Point (COC)	ASTM D92	°C	228
CCS @-30°C	ASTM D5293	mPas (cP)	6265
TBN	ASTM D2896	mg KOH/g	8.0

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.